

# 3D IS **SO** YESTERDAY.



Future-proof your installations today with 4K matrix switching at an outrageously low price!



**DL-HDM44**

**4 INPUT, 4 OUTPUT HDMI MATRIX SWITCHER WITH 4K SUPPORT**

*Perfect for Commercial and Residential Installations*



**LIBERTY**  
AV SOLUTIONS

**RUN WITH US**  
WWW.LIBAV.COM | 800.530.8998

## 4 INPUT, 4 OUTPUT HDMI MATRIX SWITCHER WITH 4K SUPPORT // DL-HDM44

Ideal for houses of worship, corporate video conferencing, boardrooms, conference centers, and residential installations.



Liberty AV Solutions introduces the latest addition to our highly successful DigitalInx line of products. With full matrix switching capabilities at an extremely affordable price, the **DL-HDM44** is a perfect choice for your budget-conscious installations.

This four input by four output HDMI matrix switcher comes standard with up to **4K video resolutions, Deep Color, and 3D video.**



The DL-HDM44 can be controlled via front panel buttons, front panel IR, external IR, RS232, and through a web browser when the matrix is connected to a network. The matrix includes a simple IR remote control to allow IR switching. The EDID settings for the matrix, either 1080p with stereo audio or the EDID of the display on Output A, are toggled by a button on the front of the matrix.

### Features & Benefits:

- 4x4 HDMI Matrix – 4 HDMI In, 4 HDMI Out
- Video support up to 4k@30hz
- Audio support up to 7.1
- IR and RS232 control
- Web GUI for control
- Extremely competitive price point

### Application:

- True matrix routing and distribution of HDMI signals
- A/V routing in environments with demanding control systems



**In Stock Now!**

Call your rep today or scan the QR code web page link.

### TECH SPECS

#### I/O CONNECTIONS

- HDMI Inputs Four (4) HDMI Type A Receptacle Connector (1 per input)
- HDMI Outputs Four (4) HDMI Type A Receptacle Connector (1 per output)
- IR Eye One (1) 3.5 mm jack (TRS)
- 5V DC Power One (1) Threaded Barrel (5.5mm OD; 2.6mm ID)
- Control, Rear Panel RS232 via DE-9, TCP/IP via 8P8C, IR via 3.5mm TRS
- Control, Front Panel Push Button, IR

#### SUPPORTED AUDIO AND VIDEO

- HDTV Video Resolutions 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4Kx2K (24, 25, and 30 Hz)
- VESA Video Resolutions Up to 1920x1200

#### SUPPORTED AUDIO AND VIDEO (CONT.)

- Maximum HDMI Distance 5m (16')
- Embedded Audio Compatibility Up to PCM 5 channel, Dolby Digital TrueHD, and DTS-HD Master Audio
- Chassis and Environmental
- Enclosure Painted Aluminum
- Dimensions 436mm x 167mm x 44mm (17.17" x 6.57" x 1.73")
- Rack Spacing 1 RU
- Shipping Weight 1.945 kg (4.3 lbs)
- Operating Temperature 0° to +40° C (+32° to +104° F)
- Operating Humidity 20% to 90%, Non-condensing
- Storage Temperature -10° to +60° C (+14° to +140° F)
- Storage Humidity 20% to 90%, Non-condensing

#### POWER, ESD, AND REGULATORY

- Power Supply Input 100V-240VAC / 50-60 Hz / 0.5A
- Power Supply Output 5VDC / 3.6A
- Power Consumption 38 watts (max)
- ESD Protection ±8kV (air-gap discharge), ±4KV (contact discharge)
- DL-HDM44 Regulatory CE, RoHS
- Power Supply Regulatory UL, FCC, CE, RoHS

#### OTHER

- Warranty 2 years
- Diagnostic Indicators LED output status, power LED, status LED
- Included Accessories Installation Guide, IR Remote, US Power Cable and Power Supply, Two Mounting Brackets, Four Rubber Feet (installed on matrix)

DL-HDM44 L0107 MAY 2014



**LIBERTY**  
AV SOLUTIONS

**RUN WITH US**  
WWW.LIBAV.COM | 800.530.8998