



# HDMI OVER 1 TWISTED PAIR

## PRODUCT SPOTLIGHT

## TRANSMIT AND/OR RECEIVE HDMI OVER A SINGLE TWISTED PAIR CABLE



When used with a compatible transmitter, the Intelix DIGI-HD-UHR2-R transmits HDMI up to 300' over a single twisted pair cable. Built-in HDshak® processing provides dynamic HDMI, EDID/DDC and HDCP mode selection, guaranteeing performance and image quality.

Plus, onboard HDMI amplification and buffering allows multiple extenders to be daisy-chained for greater distances. The DIGI-HD-UHR2-R features electrostatic discharge (ESD) protection circuitry which safeguards the HDMI circuit against static electricity and other destructive stray voltage.

**DIGI-HD-UHR2**  
(SEND AND RECEIVE SET)

**DIGI-HD-UHR2-R**  
(RECEIVE UNIT ONLY)



AVAILABLE IN  
WALLPLATE  
VERSIONS TOO!



**DIGI-HD-UHR2-WP-S**  
(RECEIVE PLATE)

**DIGI-HD-UHR2-WP-R**  
(SEND PLATE)

- Double-gang Extender wallplate
- Supports multi-channel digital audio
- May be powered from front or rear
- Supports 1080p video up to 45m (150 ft) over a single Cat6 STP

Compatible with: DIGI-HD-8X8 | DIGI-HD-XR DIGI-HD-4X8  
DIGI-HD-1x8 | DIGI-HD-4X4 | DIGI-HD-XR | DIGI-HD-4X2

- HDMI over a single twisted pair cable
- 1080p up to 45m (150 ft) via shielded CAT6A
- 720p/1080i up to 300' via shielded CAT6A
- Supported Signals: HDMI 1.3, HDCP
- HDMI amplification and buffering
- Built-in ESD surge protection



Scan code to save a text link to Liberty's DIGI-HD-UHR2 Intelix training video, or go to [www.LibAV.com](http://www.LibAV.com) for our entire video library

## DON'T FORGET THE TWISTED PAIR CABLE!



Save a text link to our twisted pair cable website section at [LibAV.com](http://LibAV.com)

