

## **AVO-V2A2-WP-F Technical Specification**

Two Channel Composite Video and Two Channel Audio Twisted Pair Wall Plate Extender Rev. 130115

The Intelix AVO-V2A2-WP-F wall plate balun transmits two composite video signals and two analog audio signals up to 2,200 feet over standard structured cabling, such as Cat 5e. Used in pairs or with the modular Intelix AVO-V2A2-F, AVO-V2A2-WP-F baluns replace bulky coaxial cable and utilize a building's existing structured cabling system.





Phone: 608-831-0880 Toll-Free: 866-462-8649 Fax: 608-831-1833



Technical Specifications		
I/O Connections	•	
Video	One (1) RCA per channel	
Audio	One (1) RCA per channel	
Twisted Pair	One (1) 8P8C port (RJ45)	
Supported Audio and Video		
Maximum Distance via Cat 5e	2200 ft.	
RJ45 Pin Configuration	Pins 1 and 2: Audio 1	
-	Pins 3 and 6: Audio 2	
	Pins 4 and 5: Video 2	
	Pins 7 and 8: Video 1	
Video Bandwidth	DC to 8 MHz	
Impedance (Video)	75 ohms	
Maximum Input Level (Video)	1.1 Vp-p	
Insertion Loss (Video)	Less than 2 dB	
Return Loss (Video)	Greater than 15 dB	
Common Mode Rejection (Video)	Greater than 40 dB	
Audio Frequency Response	20 Hz to 20 kHz	
Impedance (Audio)	600 ohms, unbalanced	
Audio Transformer Isolation	500V	
Nominal Level (Audio)	1.0 volts	
Insertion Loss (Audio)	1 dB	
Common Mode Rejection (Audio)	Greater than 40 dB	
Chassis and Environmental		
Enclosure	Galvanized Steel	
Dimensions	102 mm x 36 mm x 43 mm (4 in. x 1.4 in. x 1.7 in.)	
Shipping Weight	0.25 kg (0.56 lbs)	
Operating Temperature (Environment)	0° to +40° C (+32° to +104° F)	
Operating Humidity (Environment)	20% to 90%, Non-condensing	
Storage Temperature (Environment)	-10° to +60° C (+14° to +140° F)	
Other		
Regulatory	RoHS	
Standard Warranty	2 Years	
Included Accessories	Decora Insert, Mounting Screws, Installation Guide	
Compatible Products	AVO-V2A2-F	

Distances and picture quality may be affected by cable grade, cable quality, source and destination equipment, RF and electrical interference, and cable patches. Intelix specifications are based on straight-through cabling with standard-grade Cat 5e unless noted otherwise.



Phone: 608-831-0880 Toll-Free: 866-462-8649 Fax: 608-831-1833