Product Specification Sheet

Catalog Number: 18-25C-CM

Catalog Number: 18-25C-CM	Duadret Illestation
18 AWG Component Poly Binder Outer Jacket	Product Illustration
Physical Construction	Description
Component 1: 18 AWG 16/30 bare copper conductors SR-PVC Insulation: .017-inch nominal thickness	Communications rated multi-conductor wire for communications, control and instrumentation applications and installations in accordance with NEC article 800.
	Color Code
	Black, White, Red, Green, Brown, Blue, White/Black, Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White, Red/White, Green/White, Blue/White, Black/Red, White/Red, Orange/Red, Blue/Red, Red/Green, Orange/Green, Black/White/Red, White/Black/Red, Red/Black/White, Green/Black/White
Final assembly:	Electrical Specifications
25 of component 1 twisted in a 7.5-inch lay 100% clear Mylar tape binder PVC jacket: .045-inch nominal thickness Final construction: .598-inch nominal OD Product Print Legend: E106583 (01-12345) 18 AWG	18 AWG: DCR: 7.5 Ω per 1000 feet Voltage: 300 Volts RMS Temperature: -20°C to 60°C
TYPE CM (UL) C(UL) CMG OR AWM 2598 60C 300 VOLTS	Regulatory Specifications
Sequential footmarks are applied in conjunction with the print legend.	(UL) rated CM, AWM 2598 C(UL) rated CMG
Specification Control	Product Information
Revision Date: 04/11/2004 Liberty Wire & Cable specifications are subject to change without notice. Contact an account representative for current product specifications. Liberty Wire & Cable continuously strives to ensure product specifications are accurate and complete. All physical specifications are nominal.	Jacket Colors: Gray Packaging: 1000 foot reels Special note: 300 Volts printed on jacket in reference to the AWM 2598 certification.

Form Revision Date: 04/15/2004



FOR IMMEDIATE SERVICE FAX YOUR ORDER
719-260-0075

