




GameChanger Cable

Unshielded Twisted Pair
Plenum Rated - CMP

258300336

46224PPBLW (legacy part no)

U.S. Patent No.'s 10,453,589 & 11,107,605



1.0 Scope

1.1 This cable consists of 4 pair solid bare copper; color-coded FEP insulation; overall LSFR-PVC jacket. RoHS-2 Compliant

2.0 Construction

2.1 Conductor

- 2.1.1 Material: Bare Copper
- 2.1.2 Construction: Solid 22 AWG

2.2 Insulation

- 2.2.1 Material: Ultra Low-Loss Dielectric
- 2.2.2 O.D.: 0.044" nom
- 2.2.3 Color Code
 - Pair 1: White/Blue
Blue
 - Pair 2: White/Orange
Orange
 - Pair 3: White/Green
Green
 - Pair 4: White/Brown
Brown

2.3 Core Assembly:

2.3.1 4 twisted pairs cabled together to form the main core.

2.4 Jacket

- 2.4.1 Material: LSFR-PVC
- 2.4.2 OD: 0.248" nom
- 2.4.3 Color: Blue with a white stripe
- 2.4.4 Ripcord under jacket
- 2.4.5 Markings: "PAIGE GAMECHANGER"

PATENT NO. 10,453,589 & 11,107,605 (UL) CMP
--- C(UL) FT6 EXXXXXX ROHS SUN RES"
(Ascending/Descendinglength marking)

2.5 Electrical Properties

- 2.5.1 Conductor Resistance: $\leq 6.35\Omega/100m$
- 2.5.2 Insulation Resistance: $\geq 5000M\Omega Km$
(DC500V Charged 1 Min)
- 2.5.3 Voltage Endurance: DC 1500V/min
- 2.5.4 Mutual Capacitance: $\leq 7.0nF/100m$
- 2.5.5 Core-Core Resistance Unbalance: $\leq 5\%$
- 2.5.6 Maximum Voltage: 300V (Per NEC, not suitable for Class 1 power applications)

2.6 Temperature Rating

- 2.6.1 $-20^{\circ}C$ to $+75^{\circ}C$

2.7 Power over Ethernet Support

- 2.7.1 Class 1 - 8

3.0 Weights and Dimensions

3.1 Put Up

- 3.1.1 Length: 1,000 ft box
- 3.1.2 Weight: 32 lbs
- 3.1.3 Dimensions: 15" x 12" x 15"

We want to hear from you!

200 Sheffield St, Suite 302, Mountainside, NJ 07092

Tel: 888.423.8947 cgorders@paigeconnected.com



Frequency MHz	Return Loss ≥dB/100m	Insertion Loss ≤dB/100m	NEXT ≥dB/100m	PSNEXT ≥dB/100m
1	24	1.5	90	87
10	31	4.8	75	72
20	32	7.0	64	61
100	26	16.1	50	47
200	24	23.2	48	45
250	21	26.1	47	44
350	20	31.4	45	42
500	19	38.3	43	40
550	18	40.4	42	39

*Values above 250 MHz are for engineering information only

Application

GameChanger cabling is designed specifically for transmitting Ethernet and can support all 8 classes of Power over Ethernet.

GameChanger Cable can deliver 2.5Gbps and 100W PoE up to 656 feet (200m) or if you need to go farther, GameChanger Cable can deliver 10Mbps and 100W PoE up to 850 feet (259m).

Connectors

GameChanger cables have 22 AWG conductors. So when punching down to a jack or a patch panel, any Cat6 connectivity will work. If you are using a RJ45 connector, check out this termination guide: <https://paigedatacom.com/uploads/Media/4/GameChanger%20Termination%20Guide.pdf>



Alternate Constructions

GameChanger cabling is also available with:

- 258310333 - Riser, Yellow w/ White Stripe
- 258300336 - Plenum, Blue w/ White Stripe
- 258300310 - Plenum, White
- 258330804 - OSP, Black
- 258340804 - OSP Shielded, Black
- 258802404 - Class I, Division 1 Armored

Frequently Asked Questions

For FAQ and best practices please visit: www.paigedatacom.com/gamechanger

We want to hear from you!

200 Sheffield St, Suite 302, Mountainside, NJ 07092

Tel: 888.423.8947 cgorders@paigeconnected.com
www.paigedatacom.com/gamechanger

