



**Technical Specifications**

**Product Line: 4FRIOMM6-D**

**Description**

4 fiber 62.5/125 OM1 multimode distribution cable

NEC type OFNR and CEC type FT4. Sunlight resistant and water blocked for indoor and outdoor applications. Product manufactured compliant to the requirements of UL1651 for installations and applications in accordance with NEC article 770.

**Fiber Type**

OM1 62.5/125 multimode fiber

**Optical Characteristics**

Numerical aperture:	0.275	
Wavelength:	850nm	1310nm
Gigabit ethernet distance:	300m	600m
10 Gigabit ethernet distance:	33m	300m (laser)
Maximum attenuation:	3.5 dB/Km	1.5 dB/Km
Min Laser bandwidth:	500 MHz/Km	500 MHz/Km
Min LED bandwidth:	200 Mhz/Km	500 MHz/Kz

**Buffer**

Primary buffer UV cured acrylate

Diameter: 0.245µM

Secondary buffer polyvinyl chloride

Diameter: 0.900µM

**Regulatory**

NEC: OFNR 75 °C

CEC: FT4 60 °C

Sunlight resistant

Suitable for wet locations

EU RoHS 2002/95/EC Compliant

**Color Code**

Buffer: Blue, Orange, Green, Brown

**Packages**

Reel: Fiber is cut to order

Weight: 16 Lbs/1000' | 24 Kg/KM

**Subassembly**

Dry core water blocked

**Installation**

Maximum pull specification: 310 lbs | 1400 N

Maximum operating load: 100 lbs | 450 N

Minimum pull radius: 3.0" | 7.70cm

Minimum operating radius: 2.0" | 5.10cm

Flex life: Min 2000 cycles

Impact resistance: 1500 impacts

Crush resistance: 1800 N/cm

Install temperature: -10 °C to +60 °C

Operating temperature: -40 °C to +85 °C

**Final Assembly**

4 Buffered fibers cabled with strength members around a central strength member

**Applications**

Riser LAN systems 10/100/1000BaseT

Riser high definition media

Riser audio/video over fiber, security and gate systems

**Construct**

Ripcord under jacket

**Performance**

1G networking 600m

**Jacket**

UV stabilized polyvinyl chloride

Colors: Black

Wall thickness: 0.022" | 0.56mm

Diameter: 0.200" | 5.10mm

**Final Outside Diameter (inches)**

0.200





**Technical Specifications**

**Product Line: 4FRIOMM6-D**

Specification Revision Date:

October 28, 2008

