



Technical Specifications

Product Line: RG6-CM-SIAM

Description

Dual 18 AWG solid core CCS dual shielded RG6 CATV/DBS coaxial cable
NEC type CM and CEC type CMG FT4. Product manufactured compliant to the requirements of UL444 for installations and applications in accordance with NEC articles 725, 800 and 820.

Conductor

18 AWG
Solid copper clad steel conductors
Diameter: 0.040" | 1.02mm

Electrical

DC resistance: 36.28 Ω / 1000' | 119 Ω /KM
Shield DCR: 9.70 Ω / 1000' | 31.80 Ω /KM
Mutual capacitance: 16.2 pF/FT | 53.1 pF/M
Impedance: 75 \pm 3 Ω
Velocity of Propagation: 80%
Voltage rating: 300V
SRL 5-2200 MHz: -20dB
SRL 2.2-3 GHz: -17dB

Insulation

Foam polyethylene
Wall thickness: 0.070" | 1.78mm
Diameter: 0.180" | 4.57mm

Regulatory

NEC: CL2 60°C
EU RoHS 2002/95/EC Compliant

Color Code

Natural

Packages

Reel: 1000' | 305M
Weight: Lbs/1000' | Kg/KM

Assembly

two jacketed RG6 dual shield cables ran in parallel and joined by a web

Installation

Pull Tension: 252 Lbs | 1120 N
Bend radius: 5.63" | 143mm unloaded
Bend radius: 11.26" | 286mm loaded

Construct

N/A

Applications

General purpose CATV and DBS modulated video
General purpose CATV and DBS where DC is not required
General purpose Broadband video and cable modem

Shield

100% aluminum/poly
60% 34 AWG aluminum braid shield

Performance

CATV to 237 feet
DBS to 158 feet

Jacket

Flame retardant polyvinyl chloride
Colors: Black
Wall thickness: 0.032" | 0.813mm
Diameter: 0.274x0.563" | 6.96x14.30mm

Final Outside Diameter (inches)

0.274x0.563

Specification Revision Date:

August 4, 2010





Technical Specifications
Product Line: RG6-CM-SIAM

RG6 Coaxial Sweep to 3.0 GHz

Frequency	Attenuation	
	dB/100FT	dB/100m
1	0.28	0.92
50	1.46	4.79
100	2.04	6.69
200	2.83	9.28
400	4.05	13.28
900	6.23	20.43
1000	6.59	21.62
1450	7.93	26.01
1800	8.83	28.96
2200	9.76	32.01
3000	13.26	43.49

