Product Specification Sheet

Catalog Number: RGB3C-20-CMR	
Construction Detail	Product Illustration
Outer Jacket Binder Filler Coaxial Component Ripcord	
Physical Construction	Description
Component 1: Single coax 20 AWG solid bare copper center conductor Foam Polyethylene dielectric: .145-inch nominal diameter 100% Bonded Aluminum/Poly/Aluminum inner shield 95% 36 AWG tinned copper braid outer shield FR-PVC jacket: .032-inch nominal thickness Coaxial construction: .242-inch nominal OD	Communications riser rated RGB RG59/U precision video coaxial cable for Analog audio/video, Digital audio/video, HDTV/SDI, Broadcast, Broadband and Baseband video installations in accordance with NEC article 800. A superior RGB cable solution for all 75 Ω RG59 non-plenum applications.
	Color Code
	Red, Green, Blue
	Electrical Specifications
Final assembly: 3 of component 1 planetary cabled with fibrillated PVC fillers as needed for roundness 100% Mylar tape binder with 25% overlap 100% Paper tape binder with 25% overlap Nylon ripcord under the jacket. TPE jacket: .055-inch nominal thickness Final construction: .630-inch nominal OD Product Print Legend: LWC P/N RGB3C-20-CMR 20 AWG CMR (UL) C(UL) E190606-C Sequential footmarks are applied in conjunction with the print legend every two feet in white ink.	Coaxial: ATTENUATION Conductor DCR: 10.0 Ω per 1000 feet MHz dB/100Ft feet 1.0 0.29 Shield DCR: 3.4 Ω per 1000 feet 10.0 0.84 Capacitance: 16.3 pF per foot 100.0 2.58 Voltage: 300 Volts RMS 270.0 3.80 Impedance: 75 ± 3 Ω Nom. 540.0 5.47 Temperature: -30°C to 75°C 750.0 6.50 VOP: 83% Nom. 1000.0 7.60 SRL: 26dB min. up to 500MHz. 2000.0 10.90 20dB min. up to 3.0GHz. 3000.0 13.40 Regulatory Specifications NEC rated CMR CEC rated CMR EU RoHS 2002/95/EC Compliant since 05/10/2006
Specification Control	Product Information
Revision Date: 04/11/2009 Liberty Wire & Cable specifications are subject to change without notice. Contact an account representative for current product specifications. Liberty Wire & Cable continuously strives to ensure product specifications are accurate and complete. All physical specifications are nominal.	Jacket Colors: Black Packaging: 500 foot reels

Form Revision Date: 04/15/2004



FOR IMMEDIATE SERVICE FAX YOUR ORDER

