



Technical Specifications

Product Line: TEKTONE-P2

Description

3 conductor stranded, twisted, and shielded cable.

NEC type CMR and CEC type CMG FT4. Product manufactured compliant to the requirements of UL444 for installations and applications in accordance with NEC articles 725 and 800.

Conductor

18 AWG

7-strand annealed bare copper conductors

Diameter: 0.048" | 1.22mm

Insulation

Polyvinyl chloride

Wall thickness: 0.010" | 0.25mm

Diameter: 0.068" | 1.73mm

Color Code

Red, Brown, Blue

Assembly

N/A

Construct

Ripcord under jacket

Shield

100% aluminum/poly tape with foil out

20 AWG 7-strand tinned copper drain wire

Jacket

Polyvinyl chloride

Colors: Green

Wall thickness: 0.015" | 0.38mm

Diameter: 0.175" | 4.45mm

Specification Revision Date:

Electrical

DC resistance: 6.66 Ω / 1000' | 21.84 Ω /KM

Mutual capacitance: 54.0 pF/FT | 177.12 pF/M

Shield capacitance: 98.0 pF/FT | 321.44 pF/M

Impedance: 63 Ω

Velocity of Propagation: 55%

Voltage rating: 300V

Maximum current: 3.75A@25° C

Regulatory

NEC: CMR 75° C

CEC: CMG FT4 60° C

EU RoHS 2002/95/EC Compliant

Packages

Reel: 1000' | 305M

Weight: 31 Lbs/1000' | 46 Kg/KM

Installation

Pull Tension: 40 Lbs | 178 N

Bend radius: 1.75" | 45mm unloaded

Bend radius: 3.50" | 90mm loaded

Applications

Riser and GP power for TekTone® Systems

Riser and GP control and instrumentation

Riser and GP Class 2 and Class 3 power

Performance

N/A

Final Outside Diameter (inches)

0.175

June 15, 2005

