



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Fixed Wall Mount for 26" to 55" Flat-Screen Displays

MODEL NUMBER: DWF2655X











Highlights

- REPLACES MODEL DWF2647X
- Low-profile mounting keeps unit out of sight for sleek, professional appearance
- Fits most flat-panel displays from 26" to 55"
- Open frame for easy wall access
- Horizontal adjustment compensates for off-center wall studs
- Equipped with a bubble level for accurate display leveling
- Supports up to 165 lb
- 5-year warranty

Package Includes

- DWF2655X Fixed Flat-Screen
 Wall Mount
- Mounting Hardware
- Owner's Manual

Description

Tripp Lite's VESA-compliant DWF2655X Fixed Flat-Screen Wall Mount's low-profile design features an open frame for easy wall access and optimal display positioning flexibility. Its durable, all-metal construction with scratch-resistant, powder-coat finish supports weights of up to 165 lbs. and fits most 26- to 55-inch flat-panel displays. It comes with all necessary mounting hardware and features horizontal adjustment to compensate for

off-center wall studs. A built-in bubble level enables accurate display leveling. For peace of mind, the DWF2655X comes backed by a 5-year warranty and green, RoHS-compliant design.

Specifications

General Info	
Product Group	DISPLAY MOUNTS
TAA Compliant	No
OVERVIEW	
Mounting Location	Wall
Display Mount Type	Wall Mount
PHYSICAL	
Unit Weight (lbs.)	4.51
Unit Weight (kg)	2.04
Color	Black
Monitor Display Size (in.)	26 - 55



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

66.04 - 139.70	
200x100; 200x200; 400x200; 400x400	
Fixed	
N/A	
N/A	
165	
75	
SPECIAL FEATURES	
0	
0	
0	
FEATURES/SPECIFICATIONS	
Yes	
No	
WARRANTY	
5-year limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.