

3 Outlet, Direct Plug-In, 660 Joules - Protect It! Surge Suppressor

MODEL NUMBER: **SK3-0**



Highlights

- 3 outlets/direct plug-in
- 660 joule rating
- Diagnostic LEDs
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

- Ideal for any desktop, network or home computing application requiring AC protection

Package Includes

- SK3-0 surge suppressor

Description

The SK3-0 surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 3 outlets and 660 joules of surge energy absorption. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 3 outlets / direct plug-in
- Surge suppression rating: 660 joules
- EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

SELECTOR	
Selector Type	SURGE SUPPRESSORS
General Info	
Product Group	SURGE PROTECTORS
SELECTOR	
Digital Load Meter	No
Redundant Power Cords	No
SNMP Compatible	No



General Info	
TAA Compliant	No
OVERVIEW	
Intended Application	Home/Office
Style	Direct Plug-In
Surge Style	DIRECT PLUG-IN
Surge Type	Mobile; Protect It!
OUTPUT	
Frequency Compatibility	60 Hz
Output Receptacles	(3) 5-15R
Output (Watts)	1875
Circuit Breaker (amps)	15
Outlet Quantity / Type	3 NEMA 5-15R
Number of Outlets	3
Outlet Type	NEMA 5-15R
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V
Input Connection Type	NEMA 5-15P input plug
Input Plug Features	120V, 15A
Input Cord Length (ft.)	0
Input Cord Length Details	Direct Plug-In
Voltage Compatibility (VAC)	120
Maximum Surge Amps	39000
UPC ASSIGNMENT	
Unit Carton UPC#	037332148308
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	660
AC Suppression Response Time	< 1ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
Clamping Voltage (RMS)	150



AC Suppression Surge Current Rating	27,000
UL1449 Let Through Rating	500, 400, 500
Immunity	Conforms to IEE 587/ANSI C62.41
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Unit Dimensions (hwd / in.)	2.5 x 3.8 x 2.1
Unit Dimensions (hwd / cm)	6.35 x 9.7 x 5.33
Unit Weight (lbs.)	.20
Unit Weight (kg)	.09
Material of Construction	Plastic
Integrated Keyhole Mounting Tabs	Direct plug-in suppressor mounts directly to a wall receptacle
Housing Color	Light Gray
Receptacle Color	Gray
SPECIAL FEATURES	
KVM Demo Flag	0
Console Server Demo Flag	0
US & Canada Only Flag	0
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$5,000 Ultimate Lifetime Insurance