

Power It! Safety Power Strip with 8 Outlets and 25-ft. Cord with GFCI Plug

MODEL NUMBER: TLM825GF



Highlights

- 8 outlets (including transformer outlets and 4 safety covers)
- 25 ft. extra-long cord with GFCI plug
- Cord wrap with hang holes
- · Rugged metal case

Applications

- Industrial
- Automotive
- Factory
- Hardware

Package Includes

- TLM825GF Safety Power Strip
- 4 safety covers
- Owner's manual

Description

This Tripp Lite power strip is designed to safely distribute power to connected equipment in harsh environments. It provides a convenient source for multiple outlets wherever they're needed. 8 outlets distribute AC power to a wide range of power tools, pumps, machinery, air compressors and more. Convenient transformer outlets accommodate multiple transformers without blocking other outlets. A 25 ft. grounded cord with integrated cord clip reaches distant outlets. A GFCI plug protects users from electrical shock in wet or humid environments. A lighted on/off switch provides power control over connected equipment. 4 safety covers shield unused outlets from debris and accidental contact. A rugged metal case stands up to the harshest environments. Built-in cord wrap with hang holes provides convenient cord management. Integrated keyhole slots on bottom panel provide convenient wall/desk mounting. Its bright yellow color alerts you and others that power cords and tools are in use.

Features

- 8 outlets distribute AC power to a wide range of power tools, pumps, machinery, air compressors and more.
- Convenient transformer outlets accommodate multiple transformers without blocking other outlets.
- . A 25 ft. grounded cord with integrated cord clip reaches distant outlets.
- A GFCI plug protects users from electrical shock in wet or humid environments.
- A lighted on/off switch with integrated 15 amp circuit breaker provides power control and overload protection over connected equipment.
- 4 safety covers shield unused outlets from debris and accidental contact.
- A rugged metal case stands up to the harshest environments.
- Built-in cord wrap with hang holes provides convenient cord management.
- Integrated keyhole slots on bottom panel provide convenient wall/desk mounting.
- Its bright yellow color alerts you and others that power cords and tools are in use.
- OSHA color guidelines, outlined in Document 1910.145, alert users to hazardous situations, which may cause minor or moderate injury. This Tripp Lite
 product complies with those guidelines.

Specifications



Selector Type POWER STRIPS General Info Product Group POWER STRIPS TAA Compliant No OVERVIEW Intended Application Safety: Industrial/Factory Floor Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (ft.) 25 Input Cord Length (ft.) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120 GFCI Plug Yes	SELECTOR		
Product Group POWER STRIPS TAA Compliant No OVERVIEW Intended Application Safety; Industrial/Factory Floor Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Connection (1) Input Cord Length (ft.) 25 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
TAA Compliant No OVERVIEW Intended Application Safety; Industrial/Factory Floor Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Intended Application Safety; Industrial/Factory Floor Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (ft.) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Intended Application Safety; Industrial/Factory Floor Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Suge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Style Strip Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Power Strip Type Safety OUTPUT Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (ft.) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Cutput Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Frequency Compatibility 60 Hz Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Circuit Breaker (amps) Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Overload Protection GFCI plug Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Outlet Quantity / Type 8 NEMA 5-15R Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Number of Outlets 8 Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Transformer Accommodation Yes (3) Outlet Safety Covers Yes (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Outlet Safety Covers Ves (4) Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Outlet Orientation 1 bank of 5, 1 bank of 3 (transformer outlets) INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Recommended Electrical Service 120V, 15A Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120	INPUT		
Input Connection Type GFCI 5-15P Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Input Plug Features Integrated cord clip plus GFCI breaker Input Cord Length (ft.) 25 Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Input Cord Length (ft.) Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Input Cord Length (m) 7.62 Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120			
Voltage Compatibility (VAC) 120			
GFCI Plug Yes			
LEDS ALARMS & SWITCHES			
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch	ch		





PHYSICAL		
Shipping Dimensions (hwd / in.)	12.43 x 11.44 x 2.17	
Shipping Dimensions (hwd / cm)	31.57 x 29.06 x 5.51	
Shipping Weight (lbs.)	5.18	
Shipping Weight (kg)	2.35	
Unit Dimensions (hwd / in.)	10.26 x 5.13 x 1.57	
Unit Dimensions (hwd / cm)	26.06 x 13.03 x 3.99	
Unit Weight (lbs.)	4.63	
Unit Weight (kg)	2.10	
Material of Construction	All-metal	
Integrated Keyhole Mounting Tabs	Yes	
Receptacle Color	black	
Color (AC Line Cord)	yellow	
Outlets Measurement (Center to Center)	Distance between standard outlets = 25.40mm; Distance between transformer outlets = 50.80mm	
Keyhole Slot Mounting Measurement (Center to Center)	145mm	
SPECIAL FEATURES		
Console Server Demo Flag	0	
US & Canada Only Flag	0	
KVM Demo Flag	0	
CERTIFICATIONS		
Approvals	cULus, RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.