



DR DN® DE ORION IMAGES CORPORATION

8-inch Temperature Screening Kiosk









8FIDKR



BUILT TO RUN 24 x 7 x 365 CONTINUOUSLY

OVERVIEW

Health and safety in the workplace are clear priorities, now and in the future. This contactless infrared temperature measuring interactive kiosk is an AI based solution for visitor access and monitoring. Functions include an alarm system, facial recognition, mask recognition, and temperature detection. All of this is capable with one system - the ORION temperature screening kiosk.

SPECIAL FEATURES









RECOGNITION

MODE

REGISTER/DATA STORAGE

DETECTION

RELAY/WIEGAND





TEXT AND E-MAIL ALERTS

REMOTE SOLUTION

USED IN ANY ENVIRONMENT

- Schools, universities, and academies
- Office buildings
- Churches, temples, and museums
- Government offices
- Shopping malls and stores
- Hospitals
- Transportation hubs











8FIDKR

SPECIFICATIONS

8FIDKR	
Screen	
Size	8.0 inch IPS LCD screen
Resolution	800×1280
Processors	
CPU	RK3288 Quad core processor
Local storage	EMMC 8G
Interface	
Network module	Ethernet
Audio	2.5 W/4R speakers supported
USB interface	USB OTG,1 Road USB HOST Standard A Pass
Serial communication	1 RS232 serial port
Relay output	1 door open signal output
Upgrade button	Support Uboot upgrade keys
Wired Network	1 RJ45 Ethernet
Camera	
Resolution	200W pixels
Type	Binocular wide dynamic camera
Aperture	F2.4
Focus distance	1.64~4.92ft 50~150 cm)
White balance	Automatic
Light-up lamp	LED and infrared dual light
Function	EED did iimaist daariigiit
Identification distance configuration	Support
UI interface configuration	Support
Remote upgrade of equipment	Support
Body Temperature Testing	Support
Infrared thermal imaging	
Temperature detection distance	3.281 ft / 1m (best distance 1.64 ft/ 0.5 m)
Measurement accuracy	≤ 0.9°F (0.5°C)
Temperature measurement range	50~107.6°F (10°C~42°C)
Pixel points	32X 32 lattice (total 1024 pixels)
Over temperature alarm	Support (temperature alarm can be set)
Conventional parameters	
Power supply	DC12V (±10%)
Working temperature	32~104°F (0°C~40°C)
Storage temperature	-4~140°F (-20°C~60°C)
Power consumption	13.5W (Max)
Installation	Options (table/floor)
Dimensions	0.972x0.436x0.082ft (296.18*132.88*25mm)
Packing list	The second second residence for the second s
Packige	Machine x 1, power adapter x 1, base x 1
Display package size	1.394x0.554x0.367ft (425x169x112mm)
A08F base packing size	4.216x1.41x1.23ft (1285*430*375 mm)

REMOTE SOLUTION




Orion Images developed remote programs that can provide real-time monitoring, access control, and user registration through a PC.


INPUT INTERFACE



DIMENSIONS







Floor stand Model