## **Extending USB Signals Comparison Table**

Liberty's USB Point-to-Point Signal Extension

LIBERTY AV SOLUTIONS www.libav.com 800-530-8998 Liberty AV offers high-grade USB extenders that provide a simple and flexible solution for any USB application, including education, commercial, and medical. Go beyond the 5-meter limitation only using one category cable, providing you the ability to extend USB peripherals 10+ meters away from the host computer. We make it easier to connect and extend various USB peripherals to your laptop or personal computer (such as web cameras, microphones, cable cards, and disk drives). Truly plug-and-play; no driver is required when extending devices to use with software platforms such as Zoom, Teams, YouTube, FaceTime, and other messaging applications.

|                              | CLEAT<br>MALANA<br>MALANA<br>MALANA<br>MALANA |         | TOP<br>TOP<br>TOP |                  |                  |                  |                   |                   |                  |                  |                   |
|------------------------------|---|---------|-------------------|------------------|------------------|------------------|-------------------|-------------------|------------------|------------------|-------------------|
| !                            | BASIC   |         |                   |                  |                  | ERMEDIATE        |                   | 1                 |                  | ADVANCED         |                   |
| MODEL                        | PMI-A9  | AVO-USB | DIGI-USB2         | DIGI-USB2-4P     | INT-USB2-50C***  | INT-USB2-50H***  | INT-USB2-50CWP*** | INT-USB2-50HWP*** | INT-USB3.1CX     | INT-USB3.1-ARJ   | INT-USB3.1CX-PLUS |
| Data Transfer Rate           | 12 Mbps                                       | 12 Mbps | 480 Mbps          | 480 Mbps         | 480 Mbps         | 480 Mbps         | 480 Mbps          | 480 Mbps          | 5 Gbps           | 5 Gbps           | 5 Gbps            |
| USB 3.x Client Ports*        | Х   | Х       | х                 | Х                | х                | х                | х                 | х                 | 4                | 1                | 4                 |
| USB 2.0 Client Ports         | 1   | 1       | 1                 | 4                | 2                | х                | 2                 | х                 | •                | •                | •                 |
| USB 3.x Host Ports           | х   | х       | х                 | Х                | Х                | Х                | х                 | x                 | 1                | 1                | 1                 |
| USB 2.0 Host Ports           | 1   | 1       | 1                 | 1                | Х                | 1                | х                 | 1                 | 1                | 1                | 1                 |
| 10m Transmission Range       | ٠   | ٠       |                   |                  |                  |                  |                   | ٠                 | •                |                  |                   |
| 50m Transmission Range       |   | •       |                   |                  |                  |                  | ٠                 |                   |                  | Х                | •                 |
| 100m Transmission Range      |   | •       | •                 |                  | х                | Х                | х                 | x                 | •                | Х                | •                 |
| Isochronus 2.0 Data Transfer | х   | х       |                   |                  |                  |                  | •                 |                   |                  |                  | •                 |
| Isochronus 3.x Data Transfer | х   | х       | х                 | х                | х                | х                | x                 | Х                 | х                |                  | •                 |
| USB Compliance               | 1.x   | 1.x     | 2.0, 1.x          | 2.0, 1.x         | 2.0, 1.x         | 2.0, 1.x         | 2.0, 1.x          | 2.0, 1.x          | 3.x, 2.0, 1.x    | 3.x, 2.0, 1.x    | 3.x, 2.0, 1.x     |
| Wall Plate                   | Optional**                                    | х       | х                 | Х                | Х                | Х                |                   | •                 | Х                | Х                | x                 |
| Extender Set                 | Х   | х       | •                 |                  | Х                | Х                | x                 | x                 | •                | •                | •                 |
| Cable Type                   | Cat5e+  | Cat5e+  | Cat5e+            | Cat5e+           | Cat5e+           | Cat5e+           | Cat5e+            | Cat5e+            | FTP Cat6a +      | Provided 10m     | FTP Cat6a +       |
| Provided Host USB Cable      | Х   | х       | •                 | •                | Х                |                  | Х                 | •                 | •                | •                | •                 |
| Power Delivery****           | N/A   | N/A     | 5 V 500 mA 2.5 W  | 5 V 500 mA 2.5 W | 5 V 500 mA 2.5 W | 5 V 500 mA 2.5 W | 5 V 500 mA 2.5 W  | 5 V 500 mA 2.5 W  | 5 V 900 mA 4.5 W | 5 V 900 mA 4.5 W | 5 V 900 mA 4.5 W  |
| Bulk Transfer                | х   | Х       | •                 |                  |                  |                  | •                 |                   |                  |                  | •                 |

\*USB 3.0 is backwards-compatible with USB 2.0 and 1.x \*\* Can be purchased as a wall plate or traditional black box. \*\*\*Client and host extender set purchased separately. \*\*\*\*USB specification and maximum voltage, current and power.

03.2022\_v1