

# **Residential Speaker Cables**







When Audio ConnecTec<sup>™</sup> is combined with Liberty's UltraCap THX<sup>™</sup> certified speaker cable for use with external speakers, sonic fidelity is noticeably enhanced.

# UltraCap™ Premium Speaker Cable Non-Plenum, THX™ Certified

- Liberty's premier speaker cable
- THX<sup>TM</sup> certification assures sonic integrity
- Exceptional high strand count
- Tight inner conductor twisting
- Low capacitance

- The jacket on this cable has a superior feel
- · Very easy to work with
- UL listed NEC type CL3 or CM
- · Available in 2 colors

AWG/Pairs	Stranding	Color	Put-up	Part#
16/1	105 x 36	White	1,000 ft.	16-1P-UC-WHT
14/1	168 x 36	White	1,000 ft.	14-1P-UC-WHT
14/1	168 x 36	Black	1,000 ft.	14-1P-UC-BLK
14/2	168 x 36	Black	500 ft.	14-2P-UC-WHT
12/1	261 x 36	White	1,000 ft.	12-1P-UC-WHT
12/1	261 x 36	Black	1,000 ft.	12-1P-UC-BLK
12/2	261 x 36	White	500 ft.	12-2P-UC-WHT




White (WHT)

### Multi-Room Audio, Single-Room **Audio &** Large Homes








### Why OFC is Better

When audio signals move through a normal piece of copper cable they encounter layers of copper crystals which act as a barrier reflecting and degrading the signal. OFC copper reduces the amount of crystals in the copper for a clearer signal.



OFC Copper - Better Signal



### **ExtraFlex™ Premium Speaker Cable Non-Plenum**

- Best selling speaker cable
- Oxygen-free Copper (OFC)
- High strand counts
- · Extra thick extruded PVC compound outer cable jacket
- Extremely flexible
- · Perfectly round

AWG/

- Jacket keeps conductor twists in place to protect the sonic fidelity
- Exceptionally easy to pull
- · Designed for heavy duty distributed audio applications
- UL listed NEC type CL3 or CM
- Available in 6 colors

Conductors	Stranding	Color	Put-up	Part#
16/2	105 x 36	Black, Green, Pink, Royal Blue, Teal, or White	1,000 ft.	16-2C-EX+ -*
16/4	105 x 36	Black, Green, Pink, Royal Blue, or White	1,000 ft. or 500 ft.	16-4C-EX+ -*
14/2	105 x 34	Green, Pink or White	1,000 ft.	14-2C-EX+-*
14/4	105 x 34	Green, Pink or White	500 ft.	14-4C-EX+ -*
12/2	105 x 32	Teal or White	500 ft.	12-2C-EX+ -*
12/4	105 x 32	Teal or White	500 ft.	12-4C-EX+ -*
10/2	105 x 30	White	500 ft.	10-2C-EX+ -WHT

Asterisk (*) equals color. See color abbreviations. Example: 12-4C-EX+ -TEA					
Black	Green	Pink	Royal Blue	Teal	White (WHT)
(BLK)	(GRN)	(PNK)	(RBL)	(TEA)	





✓ Super easy to pull ✓ 6 colors ✓ Extra thick jacket **✓** Extremely flexible

✓ 105 Strand Count

✔ Performance

✓ Oxygen free copper (OFC)








# **Residential Speaker Cables**

AWG/







#### **KO+™ Speaker Cable** Non-Plenum

- Higher strand count than
- HomeTRAX<sup>TM</sup> • Residential audio workhorse
- · Designed for medium duty
- · Meets a variety of in-wall distributed audio requirements.
- UL listed NEC type CL3 or CM
- Available in 5 colors

Conductors	Stranding	Color	Put-up	Part#
16/2	65 x 34	Light Blue or White	1,000 ft.	16-2C-KO+ -*
16/4	65 x 34	Gray, Light Green or White	1,000 ft. or 500 ft.	16-4C-KO+ -*
14/2	65 x 32	Black or White	1,000 ft.	14-2C-KO+ -*
14/4	65 x 32	White	500 ft.	14-4C-KO+ - WHT

Asterisk (\*) equals color. See color abbreviations.

Example: 16-2C-KO+ -LBL





**Light Blue** 

Light Green

White (WHT)







#### HomeTRAX™ Speaker Cable **Non-Plenum**

- Bid on and win production home pre-wires
- Lower strand count is designed for budget conscious projects
- Price performer for budget conscious projects
- UL listed NEC type CL3 or CM
- Available in one color: white

Cross-Section View
Ripcord
14 AWG Componen
Outer Jacket

#### AWG/

Conductors	Stranding	Put-up	Part#
16/2	41 x 32	1,000 ft.	16-2C-HT
16/4	41 x 32	500 ft.	16-4C-HT
14/2	41 x 30	500 ft.	14-2C-HT
14/4	41 x 30	500 ft.	14-4C-HT



### **Direct Burial Speaker Cable Non-Plenum**

- Designed for outdoor applications
- PE installation provides protection from underground moisture
- UL rating is suitable for indoor use
- · Available in black only
- UL listed NEC type CL3 or CM





#### AWG/

Conductors	Stranding	Put-up	Part#
16/2	19 x 29	1,000 ft.	16-2C-DB-BLK
16/4	19 x 29	1,000 ft.	16-4C-DB-BLK
14/2	19 x 25	1,000 ft.	14-2C-DB-BLK
14/4	19 x 25	1,000 ft.	14-4C-DB-BLK
12/2	19 x 25	1,000 ft.	12-2C-DB-BLK
12/4	19 x 25	500 ft.	12-4C-DB-BLK





