



		RELEASE DATE
DIGI-88FS 	INTELIX FAST SWITCHING 8 × 8 HDMI MATRIX SWITCH <ul style="list-style-type: none"> Fast switching < 1 second Output scaling up to 1920 × 1200 Advanced EDID control Built-in web control 	01 SEPT 2014
DIGI-P52 	INTELIX AUTO / MANUAL PRESENTATION SWITCHER <ul style="list-style-type: none"> Automatic or manual switching: Three (3) HDMI, two (2) VGA / YUV / SVID / CVID Audio embedding & de-embedding: including mic input with phantom power Built-in scaling up to 1920 × 1200 HDBaseT with PoE (up to 60m) & HDMI output – PoE powers RX CEC control of sources from display; IR & RS232 control pass-through 	15 JULY 2014
DIGI-1X4B-1H 	INTELIX 1 × 4 HDBaseT DISTRIBUTION AMPLIFIER WITH POE <ul style="list-style-type: none"> HDBaseT DA with PoE 48V PoE for remote powering the RX Cascade out to loop to other 1 × 4 DAs RS232 and IR routing Bi-directional IR cascade EDID management Table and rack mount 	01 SEPT 2014
FLX-64 	INTELIX 6 × 4 MATRIX SWITCH WITH TWO (2) HDBaseT INPUTS <ul style="list-style-type: none"> Audio breakaway Powers remote receivers & transmitters via PoE RS232 tunneling and routing Web GUI and TCP/IP control 	01 OCT 2014
DL-HDM44 	DIGITALINX 4 × 4 HDMI MATRIX SWITCHER WITH 4K SUPPORT <ul style="list-style-type: none"> Four HDMI inputs & Four HDMI outputs Front panel, IR & RS232 control EDID management Control page and configuration accessible from web browser Supports 3D & 4k Video 	01 JUNE 2014
DL-DA12 / DA14 / DA18 	DIGITALINX HDMI DISTRIBUTION AMPLIFIER (1 × 2, 1 × 4 OR 1 × 8) <ul style="list-style-type: none"> 1 × 2, 1 × 4 or 1 × 8 HDMI distribution splitter / amplifier 1080p, 4k × 2k compatible (UHD) 10 and 12 bit color depth Automatic EDID discovery from the display Display input selection via CEC Locking power supply 	01 AUG 2014
DIGI-BSR-4K or W 	INTELIX HDBaseT RECEIVER WITH BUILT IN SCALING & POE <ul style="list-style-type: none"> "4K" SKU has built-in scaling up to 1080p / 4k × 2k "W" SKU has built-in scaling up to 1080p / 1920 × 1200 100m max distance 48V PoE for remote powering the TX SPDIF & analog audio de-embedding Compatible with Intelix point-to-point extenders, matrix switchers & presentation scalers 	01 NOV 2014
DIGI-HD60-S or R 	INTELIX 60m HDMI-IR / RS232 HDBaseT EXTENDERS & POE <ul style="list-style-type: none"> Transmitter or receiver (sold separately) HDBaseT with PoE (bi-directional power) up to 60m HDMI with CEC support REPLACES DIGI-HD70-R Locking power supply (sold separately) 	01 SEPT 2014
DL-HD70 or DL-HDE100 	INTELIX HDMI OVER TWISTED PAIR SET WITH POWER & CONTROL <ul style="list-style-type: none"> DL-HD70 – HDMI transmits up to 230ft (70m) DL-HDE100 – HDMI transmits up to 300ft (100m) & includes ethernet 1080p / 4k × 2k & 3D compatible CEC support Built-in surge suppression HDE100 Bi-directional wideband IR & RS232 pass-through Flexible power design (use power supply at TX or RX) DL-HDE100 has 100-BaseT ethernet pass-through HDCP compliant Locking power connector Diagnostic LEDs 	01 SEPT 2014
DIGI-HDX-S or R 	INTELIX 100m HDMI-IR / RS232 HDBaseT EXTENDERS WITH POE & 2X ETHERNET SWITCH <ul style="list-style-type: none"> Works with Cisco / SciAt cable boxes HDBaseT with PoE (bi-directional power); 100m Receiver has two (2) network ports REPLACES DIGI-HDE-S or R HDMI loop out for local monitor 	01 SEPT 2014



DL-DVI-S or R100 or R250



DIGITALINX DVI OVER TWISTED-PAIR EXTENDERS

- DVI and audio transmitters and receivers are sold individually
- Stereo audio (3.5mm) or digital audio (SPIDF)
- EQ and gain adjustment
- Transmission distance up to 250m
- Max resolution: 1920 x 1200

RELEASE DATE

01 JUNE 2014

DL-USB2-WP-H/C or USB2-H/C



DIGITALINX HIGH SPEED USB EXTENDERS

- 100m max distance
- High-speed USB 2.0 (480mbps)
- Wallplate units and modular units are compatible
- Powered on client side
- Wallplate units include white decorative plates
- Modular units include mounting ears

01 SEPT 2014

DL-HDV



DIGITALINX HDMI TO VGA CONVERTER

- Not HDCP compliant
- Reads display resolutions of 1920 x 1200
- No power supply required
- Ultra compact – Size comparable to HD15 connector

15 JULY 2014

DL-AR

DL-AP Apple security clamp sold separately



DIGITALINX HDMI CONFERENCE ROOM ADAPTER SECURITY RING

- Configure your choice of adapters online & get the exact ring you need
- Security loop prevents theft
- Connects to HDMI cable with secure ferrite bead
- Compatible with standard & micro HDMI cables
- Add, remove or replace adapters in the field
- Now upgraded to include Apple adapters & Apple adapter security clamp

Includes adapter for:

- Apple Certified lightning male to HDMI female & lightning female to power device
- Apple Certified 30-pin male to HDMI female & 30-pin female to power device
- DisplayPort to HDMI
- Mini DisplayPort to HDMI
- Micro HDMI D to HDMI
- Mini HDMI C to HDMI
- DVI-D to HDMI

01 AUG 2014

DL-ADR



DIGITALINX HDMI MOBILE DEVICE ADAPTER CABLE SECURITY RING *Receive a custom tag with your logo and contact info*

- Security loop with faux ferrite & five (5) adapters to HDMI
- Adapter cable DisplayPort male to HDMI female
- Adapter cable mini-DisplayPort male to HDMI female
- Adapter cable mini HDMI C male to HDMI female
- Adapter cable micro HDMI D male to HDMI female
- Adapter cable DVI-D single link male to HDMI female
- The DisplayPort adapter cables support audio
- Faux ferrite & wire loop – attach to HDMI cable
- 2 sizes of foam rubber spacers, standard & micro cable applications:
- Adapting various mobile content devices to HDMI
- Interfacing Laptops, MACs, iPads & Smartphones to HDMI
- Boardroom, Education, House of Worship, & Presentations

01 AUG 2014

D2-HDSEM-M SERIES



LIBERTY HIGH-RETENTION HDMI CABLES

- High-speed HDMI® with ethernet
- High-retention HDMI® connectors
- CL2, CMG FT4 and RoHS compliant
- Up to 2m rated for 18Gbps
- Super flexible jacket

D2-HDSEM-M-01

D2-HDSEM-M-05

SHIPPING
MID AUGUST

D2-HDSEM-M-02

D2-HDSEM-M-08

D2-HDSEM-M-03

D2-HDSEM-M-10

D2-HDSEM-M-04

E2-HDSEM-M SERIES



LIBERTY HIGH-RETENTION HDMI CABLES

- High-speed HDMI® with ethernet
- High-retention HDMI® connectors
- CL2, CMG FT4 and RoHS compliant
- Up to 2m rated for 18Gbps
- Commercial grade for the professional

E2-HDSEM-M-0.5

E2-HDSEM-M-05

SHIPPING
LATE JULY

E2-HDSEM-M-01

E2-HDSEM-M-08

E2-HDSEM-M-02

E2-HDSEM-M-10

E2-HDSEM-M-03

E2-HDSEM-M-15

E2-HDSEM-M-04

E2-HDSEM-M-20

EZ2-LINK SYSTEM



LIBERTY MODULAR INTERCONNECTION SYSTEM

- New 15-pin format for EDID VGA
- VGA, VGA with Audio, VGA with Audio plus A/V
- Backwards compatible to EZ-LINK attachments
- Available in plenum and non-plenum
- Single pull, connect and play
- Matched faceplates
- Full stereo audio

EZ2-2V2A

EZ2-FF-P-001

EZ2-VAM-P-050

NOW SHIPPING

EZ2-2V2A-035

EZ2-FF-P-035

EZ2-VF

EZ2-2V2A-050

EZ2-FF-P-050

EZ2-VM

EZ2-2V2A-P-035

EZ2-TAIL

EZ2-VM-P-035

EZ2-2V2A-P-050

EZ2-VAM

EZ2-VM-P-050

EZ2-5BM

EZ2-VAM-035

PC-EZ21000-E-T-C

EZ2-FF-035

EZ2-VAM-050

PC-EZ21520-E-T-C

EZ2-FF-050

EZ2-VAM-P-035

PC-EZ21720-E-T-C

EZ2-2V2A SYSTEM SHOWN