

intelix
DIGITAL & ANALOG DEVICES

VGA OVER TWISTED PAIR DISTRIBUTION AMP 1X4 OUTPUT

SENDS SIGNALS TO
FOUR
REMOTE LOCATIONS
FOR POINT-TO-MANY
CONFIGURATIONS

Local VGA and stereo audio outputs | Transmits signals up to 350 ft away
DIGI-VGASD2-T4



LIBERTY
AV SOLUTIONS

A SUBSIDIARY OF WESCO DISTRIBUTION, INC.

www.LibAV.com | 800.530.8998

RUN WITH US

VGA OVER TWISTED PAIR DISTRIBUTION AMP 1X4 OUTPUT

Ideal for digital signage, corporate facilities, churches, schools and conference centers.



DIGI-VGASD2-T4 - Front



DIGI-VGASD2-T4 - Back



DIGI-VGASD2-T8 Also available

DIGI-VGASD2-T4

Features and Benefits

- Transmits computer video, stereo audio, and control signals to eight remote destinations over twisted pair cable, such as Cat 5e or Cat 6
- Local VGA and stereo audio outputs
- EDID copy feature stores destination device's EDID information
- Can pass resolutions up to 1920x1200 and 20 Hz to 20 kHz audio up to 350 feet
- One way IR and RS232 extension up to 350 feet for control of displays
- Two way IR/RS232 extension available on output one

Applications

- Transmits computer video, audio and control signals to four remote destinations up to 350 feet away
- Ideal for digital signage, corporate facilities, churches, schools and conference centers
- Designed for point-to-many configurations (4 destination devices)



DIGI-VGASD2-T4

Scan to go directly to web page

Tech Specs

PART NUMBERS	AUDIO FREQUENCY RESPONSE	CONNECTORS	POWER
DIGI-VGASD2-T4	20 Hz to 20 kHz +/- 1dB	(1) Computer video input (HD15F), (1) Computer video output (HD15F), (1) Stereo audio input (3.5 mm TRS), (1) Stereo audio output (3.5 mm TRS), (1) IR input (3.5mm TRS), (1) IR output (3.5mm TS), (4) Twisted pair output (RJ45), (1) RS232 input (3 pole euroblock), (1) Power input (5.5mm coaxial power connector)	12VDC 2A
COMPATIBLE RECEIVERS	CROSSTALK	ENCLOSURE	REGULATORY
DIGI-VGASD2-R	-70 dB @ 2 kHz with a +7 dB input -65 dB @ 20 kHz with a +7 dB input	Aluminum (Painted Black)	CE, RoHS
MAXIMUM DISTANCE PER LINKED UNIT	SIGNAL TO NOISE RATIO	DIMENSIONS (INCLUDING CONNECTORS)	ESD PROTECTION
350 feet	80 dB @ 7 dBu	215mm (H) x 117mm (W) x 42mm (D)	Yes
SUPPORTED VIDEO RESOLUTIONS	REQUIRED CABLING	DIMENSIONS (INCLUDING CONNECTORS/ EARS)	DIAGNOSTIC INDICATORS
Up to 1920x1200	Cat 5, Cat 5e, Cat 6, Cat 7 compatible	242mm (H) x 117mm (W) x 42mm (D)	Power LED IR/RS232 communications LED EDID Copy LED
SUPPORTED AUDIO	UNSHIELDED TWISTED PAIR MAXIMUM CAPACITANCE	SHIPPING WEIGHT	WARRANTY
Analog stereo audio (-10dBv)	20 pf/foot	2 lbs. (0.9kg)	2 years
EDID MODES	CABLE IMPEDANCE		WHAT'S IN THE BOX
1280x800 (WXGA) Preset, 1024x768 (XGA) Preset, EDID Copy	100 ohms @ 1 MHz (24 gauge or lower solid)		(1) DIGI-VGASD2-T4, (1) 12VDC 2A Power Supply, (1) Installation Manual, (2) Mounting Brackets
VIDEO BANDWIDTH	CABLE ATTENUATION		AVAILABLE ACCESSORIES (NOT INCLUDED)
300 MHz	6.6 dB/10 feet @ 1MHz copper		VGASD2-EYE - IR Receiver VGASD2-EMT - IR Emitter



**LIBERTY
AV SOLUTIONS**

A SUBSIDIARY OF WESCO DISTRIBUTION, INC.

RUN WITH US
WWW.LIBAV.COM | 800.530.8998