

**intelix**  
DIGITAL & ANALOG DEVICES

# WIRELESS HD TRANSMISSION

**UNCOMPRESSED 1080P  
HDMI WIRELESS TRANSMISSION  
UP TO 100 FEET  
EVEN THROUGH FRAMED  
SHEETROCK WALLS**

||||| Ideal for almost any application where a wired HDMI connection is not possible | Up to 20 destinations  
**SKYPLAY-HD**



**LIBERTY**  
AV SOLUTIONS

A SUBSIDIARY OF WESCO DISTRIBUTION, INC.

[www.LibAV.com](http://www.LibAV.com) | 800.530.8998

**RUN WITH US**

# WIRELESS HD TRANSMISSION

*Ideal for almost any application where a wired HDMI connection is not possible.*

**intelix**  
DIGITAL & ANALOG DEVICES



Sold as a set or separately



Shown with included cradles



Send unit



Receive unit

## SKYPLAY-HD

### Features and Benefits

- Receives wireless transmission of uncompressed 1080p video and stereo audio up to 100 feet
- HDMI and HDCP compliant
- Supports 480i/p, 576i/p, 720p, 1080i/p, and VESA resolutions up to 1920x1080
- Can be used as a wireless HDMI distribution amplifier - up to 20 receivers per transmitter
- Less than 3ms AV latency
- Wireless signal passes through framed sheetrock walls

### Applications

- Send HDMI signal from a source to a destination device without a wired connection
- Wireless HDMI distribution amplifier - up to 20 destinations
- Ideal for residential AV, digital signage, corporate facilities, churches, schools, and almost any application where a wired HDMI connection is not possible



**SKYPLAY-HD**  
Scan to  
go directly  
to web page



**SKYPLAY-HD**  
Scan to  
go directly  
to video

## Tech Specs

### PART NUMBERS

SKYPLAY-HD-R: (1) receive  
SKYPLAY-HD-S: (1) send

### MAXIMUM DISTANCE (OPEN STRUCTURE)

1080p: 30 meters (100')  
1080i/720p: 30 meters (100')  
480i/480p/576i/576p: 30 meters (100')

### MAXIMUM DISTANCE (LIGHT CONSTRUCTION)

Dependent on barrier construction

### MAXIMUM LINKED UNITS

20

### DIMENSIONS

5.8" x 3.8" x 0.9"

### SHIPPING WEIGHT

1 lbs.

### SUPPORTED VIDEO RESOLUTIONS

480i, 480p, 576i, 576p, 720p, 1080i, 1080p  
and VESA up to 1920x1080

### SUPPORTED COLOR DEPTH

30-bit

### SUPPORTED AUDIO

2CH PCM, (Dolby D 5.1 and DTS 5.1  
if forced by source)

### 3D SUPPORT

Yes

### COMPLIANCE

HDCP 2.0

### WIRELESS TRANSMISSION TECHNOLOGY

WHD1 1.0

### SIGNAL BANDWIDTH

40 MHz

### TRANSMISSION RATE

3 Gbps

### OPERATING FREQUENCY

5.1 - 5.9 GHz

### TMDS

0.5 - 1.5 volts p-p

### DDC

5 volts p-p

### DELAY

< 1 ms

### ESD PROTECTION

IEC61000-4-2

### CONNECTORS

HDMI

### ENCLOSURE

Black Plastic

### POWER

5 VDC, 2A

### OPERATING TEMPERATURE

120° F in supplied stand  
160° F mounted flat

### REGULATORY

FCC, CE, RoHS



**LIBERTY  
AV SOLUTIONS**

A SUBSIDIARY OF WESCO DISTRIBUTION, INC.

**RUN WITH US**  
WWW.LIBAV.COM | 800.530.8998