



## CORPORATE AV SOLUTIONS

### DL-HFC



**Plenum rated Hybrid Copper / Fiber Optic HDMI with detachable heads  
EXTENDS HDMI 2.0 AND HDCP 2.2 SIGNALS UP TO 100 FEET WITHOUT  
INLINE ELECTRONICS OR SECONDARY POWER**

- Plenum rated cable for all installations
- Ultra-Small diameter cable
- Detachable HDMI TX and RX units from main body
- No external power needed, uses equipment power
- NEC CMP-OF, CEC FT6, HDCP 2.2, RoHS Compliant
- Lengths: 25, 35, 50, and 75 feet
- HDMI High Speed, 19.2Gbps, 4Kx2K@60Hz, 3D, all audio

### DL-S41



#### **4x1 HDMI Autoswitcher**

**AUTOMATICALLY SWITCH BETWEEN FOUR HDMI SOURCES FOR UNDER \$200  
ALLOWS FOUR USERS TO COLLABORATE IN A HUDDLE ROOM WITHOUT THE  
NEED FOR AN EXPENSIVE CONTROL SYSTEM**

- One HDMI and one 3.5 mm (ARC & audio de-embedding) output
- Front panel, IR and RS232 control
- UHD, 1080p, 3D compatible; HDCP compliant

### DL-AS21C



#### **HDMI + VGA Auto-Switcher with CEC Control**

**PROVIDE HDMI AND VGA CONNECTIVITY IN THE CLASSROOM FOR UNDER \$200  
ALLOWS USERS TO AUTOMATICALLY SWITCH BETWEEN ANALOG AND DIGITAL  
SIGNALS WITHOUT A CONTROL SYSTEM**

- HDMI supports 1080p, 3D and 4K video and 2.0/5.1 audio
- VGA scaling up to 1920x1200 with audio embedding
- Built-in EDID settings and EDID pass-through
- HDMI output with CEC control of display
- Manual, RS232, contact closure, & automatic switching

### DL-AS61



#### **4 HDMI + 2 VGA Input Auto-Switcher**

**ALLOWS SIX USERS TO COLLABORATE IN A HUDDLE ROOM WITHOUT  
THE NEED FOR AN EXPENSIVE CONTROL SYSTEM  
AUTOMATICALLY SWITCH BETWEEN FOUR HDMI SOURCES AND TWO  
VGA SOURCES FOR UNDER \$350**

- HDMI supports 1080p, 3D and 4K video and 2.0/5.1 audio
- VGA scaling up to 1920x1200 with audio embedding
- Built-in EDID settings and EDID pass-through
- HDMI output with analog and optical audio outputs
- Manual, RS232, IR, and automatic switching

### DL-USB3.0



#### **15 m Hybrid Fiber USB 3.0 Cable**

**EXTENDS USB 3.0 CAMERA TRANSMISSION DISTANCE UP TO 50 FEET**

- Supports USB 3.0, not backwards with USB 1.1/2.0
- Powered through USB dongle for devices drawing > 2.5W
- Locking USB 3.0 port
- Slot port for convenient cable tie mounting