



DIGI-88FS



INTELIX FAST SWITCHING 8 × 8 HDMI MATRIX SWITCH

- Fast switching < 1 second
- Output scaling up to 1920 × 1200
- Advanced EDID control
- Built-in web control

DIGI-1X4B-1H



INTELIX 1 × 4 HDBaseT DISTRIBUTION AMPLIFIER WITH POE

- HDBaseT DA with PoE
- 48V PoE for remote powering the RX
- Cascade out to loop to other 1 × 4 DAs
- RS232 and IR routing
- Bi-directional IR cascade
- EDID management
- Table and rack mount

FLX-64



INTELIX 6 × 4 MATRIX SWITCH WITH TWO (2) HDBaseT INPUTS

- Audio breakaway
- Powers remote receivers & transmitters via PoE
- RS232 tunneling and routing
- Web GUI and TCP/IP control

DL-HDM44



DIGITALINX 4 × 4 HDMI MATRIX SWITCHER WITH 4K SUPPORT

- Four HDMI inputs & four (4) HDMI outputs
- Front panel, IR & RS232 control
- EDID management
- Control page & configuration accessible from web browser
- Supports 3D & 4K Video

DL-DA12 / DA14 / DA18



DIGITALINX HDMI DISTRIBUTION AMPLIFIER (1 × 2, 1 × 4 OR 1 × 8)

- 1 × 2, 1 × 4 or 1 × 8 HDMI distribution splitter / amplifier
- 1080p, 4K × 2K compatible (UHD)
- 10 and 12 bit color depth
- Automatic EDID discovery from the display
- Display input selection via CEC
- Locking power supply

DIGI-BSR-4K or W



INTELIX HDBaseT RECEIVER WITH BUILT IN SCALING & POE

- "4K" SKU has built-in scaling up to 1080p / 4K × 2K
- "W" SKU has built-in scaling up to 1080p / 1920 × 1200
- 100m max distance
- 48V PoE for remote powering the TX
- SPDIF & analog audio de-embedding
- Compatible with Intelix point-to-point extenders, matrix switchers & presentation scalars

DIGI-HD60-S or R



INTELIX 60m HDMI-IR / RS232 HDBaseT EXTENDERS & POE

- Transmitter or receiver (sold separately)
- HDBaseT with PoE (bi-directional power) up to 60m
- HDMI with CEC support
- Locking power supply (sold separately)

DIGI-HD60C-S or R



INTELIX HDBaseT HDMI OVER TWISTED PAIR TRANSMITTER & TWISTED PAIR RECEIVER WITH POWER & CONTROL

- HDMI transmission up to 195 ft (60m)
- 1080p, 4K × 2K & 3D compatible
- CEC supported
- Built-in surge protection
- Diagnostic LEDs
- HDCP compliant
- Bidirectional Wideband IR & RS232 passthrough
- PoE (Power over Ethernet) – power from RX (PS not included) when used with DIGI-HD60C-S
- Locking Power Connector

DIGI-HDX-S or R



INTELIX 100m HDMI-IR / RS232 HDBaseT EXTENDERS WITH POE & 2X ETHERNET SWITCH

- Up to 90m (328 ft) extension of HDMI multimedia
- 100BaseT ethernet, bi-directional IR & RS232 pass-through
- Supports 3D, 4K × 2K, most audio formats up to 7.1 channel audio
- Supports Consumer Electronics Control
- Supports HDBaseT Specifications; HDMI & HDCP compliance
- Works with SciAt & Cisco cable boxes
- EDID pass through makes for a simple and easy installation



DL-HD70 or DL-HDE100



INTELIX HDMI OVER TWISTED PAIR SET WITH POWER & CONTROL

- DL-HD70 – HDMI transmits up to 230ft (70m)
- DL-HDE100 – HDMI transmits up to 300ft (100m) & includes ethernet
- 1080p/4K x 2K & 3D compatible
- CEC support
- Built-in surge suppression
- HDE100
- Bi-directional wideband IR & RS232 pass-through
- Flexible power design (use power supply at TX or RX)
- DL-HDE100 has 100-BaseT ethernet pass-through
- HDCP compliant
- Locking power connector
- Diagnostic LEDs

DIGI-44B



HDMI/HDBASET MATRIX SWITCHER 4 INPUT x 4 OUTPUT

- Bidirectional Wideband IR
- 3D Compatible
- 4 Routing Presets
- LED Readout
- Backlit buttons

DIGI-88B



HDMI/HDBASET MATRIX SWITCHER 4 INPUT x 4 OUTPUT

- Bidirectional Wideband IR
- 3D Compatible
- 8 Routing Presets
- LED Readout
- Backlit buttons
- Field replaceable cards
- RS485 Control
- Smaller profile (2RU)
- Internal Power Supply

D2-HDSEM-M SERIES



LIBERTY RESIDENTIAL GRADE HIGH SPEED HDMI® WITH ETHERNET CABLES

- High-speed HDMI® with ethernet
- High-retention HDMI® connectors
- CL2, CMG FT4 and RoHS compliant
- Up to 2m rated for 18Gbps
- Super flexible jacket

D2-HDSEM-M-01	D2-HDSEM-M-03	D2-HDSEM-M-05
D2-HDSEM-M-02	D2-HDSEM-M-04	D2-HDSEM-M-08
		D2-HDSEM-M-10

E2-HDSEM-M SERIES



LIBERTY HIGH-RETENTION HDMI CABLES

- High-speed HDMI® with ethernet
- High-retention HDMI® connectors
- CL2, CMG FT4 and RoHS compliant
- Up to 2m rated for 18Gbps
- Commercial grade for the professional

E2-HDSEM-M-0.5	E2-HDSEM-M-02	E2-HDSEM-M-08
E2-HDSEM-M-01	E2-HDSEM-M-03	E2-HDSEM-M-10
	E2-HDSEM-M-04	E2-HDSEM-M-15
	E2-HDSEM-M-05	E2-HDSEM-M-20


24-4P-L7SH-BLU



LIBERTY CATEGORY 7 HIGH BANDWIDTH

- Heavy 23' AWG pairs
- Individually shielded pairs
- Overall braid shield
- 4K HDBaseT
- UL listed bulk cable, CM and FT4
- LAN up to and beyond 10G
- Ready for 4K @ 60Hz
- Plenum coming soon!

SSF-S®



LIBERTY PREMIUM FIBER CABLE

- Integral proprietary and patented coating provides incredible glass protection
- Very small diameter distribution fiber
- Simplified termination process for greater efficiency
- Bend longevity for 10,000X longer life time than normal fibers
- Glass fiber remains protected at all times from the elements
- High mechanical strength and superior fatigue values
- Ultra low Attenuation loss on tight bend radius
- Exclusive 250um Soft peel jacket identifier in standard Fiber Color Codes